ABOVE GROUND POOLS WARREN COUNTY, OHIO

BUILDING DEPARTMENT, 406 JUSTICE DRIVE, LEBANON OH 45036

INSPECTION:

- 1. ELECTRIC TRENCH & BONDING BEFORE BACKFILLING
- 2. FINAL ELECTRIC INSPECTION.
 CALL 5136951290 THE DAY BEFORE BACKFILLING

IF YOU PLAN ANY LIGHTING WITHIN 16' OF THE POOL YOU WILL NEED TO TALK TO THE PLANS EXAMINER. 513-695-1290

NO OUTLETS WITHIN 6' OF THE POOL

CONTACT YOUR ZONING DEPARTMENT FOR FENCE REQUIREMENTS

HARD WIRED PUMP REQUIRES A SWITCH WITHIN SIGHT OF THE MOTOR. TWIST LOCK RECEPTACLE MOUNTED ON WEATHER PROOF BOX WITH COVER PUMP CONDUCTOR (WIRE) MUST REACH THE ON A 4" X 4" POST OUTLET WITHOUT AN EXTENSION CORD. IF PLUG AND CORD IS USED THE MAXIMUM LENGTH IS 3'. MUST BE BETWEEN 6' TO 10' OF POOL GFI OUTLET MOUNTED IN A WEATHER PROOF BOX WITH COVER, WITHIN 20' FROM EDGE OF POOL. 18" DEEP **CONDUIT 18" DEEP** WITH 3 #12 THWN WIRE REQUIRED: #8 COPPER BONDING CONDUCTOR 4" TO 6" **INSULATED**

THE ENTIRE POOL AND CONNECTED TO THE MOTOR GROUND.

MUST BOND ALL METAL POOL PARTS

TO THE COPPER BONDING RING

DEEP 18" TO 24" FROM THE POOL EDGE TO CIRCLE

THIS IS ONLY A PARTIAL LIST OF CODE REQUIREMENTS, REFERENCE THE OHIO BUILDING CODE AND NATIONAL ELECTRIC CODE FOR DETAILS.

